


# 32LT NATURAL GAS/PROPANE ENGINE



The PSI 32-liter is a U.S. EPA-certified natural gas and propane engine developed from the block up to be a reliable and durable power unit. Built upon a proven marine-diesel grade block, the 12-cylinder V-Configuration, turbocharged and after-cooled engine features replaceable wet liners and water-cooled exhaust.

Superior engine performance is driven by an ECU that integrates and coordinates all critical functions including: Governor, Variable Ignition Timing, Air Fuel Ratio Control, Knock Suppression and Engine Protection.

The PSI Energy product lineup has displacements from 0.97L to 65L. These engines are an extension of the PSI product line, which is based upon blocks from 650cc to 8.8L. All PSI engines feature the same fuel systems and controls, simplifying your application development and support.

## GENERAL DATA

- Turbo-charged and after cooled, cast iron with wet cylinder liners v-block
- Cast iron cylinder block with inspection door per cylinder
- Modular 4 valve cast iron cylinder heads
- Weichai supplied engine block
- High strength alloy steel forged crankshaft
- Thermostatically-controlled cooling system with engine integrated oil cooler
- Belt driven dual water pump and engine mounted fan
- J1939 CANBUS interface
- 3-Way Catalyst
- High efficiency air filter
- SAE #0 flywheel housing, SAE #18 flywheel
- Proven US ECU, fuel system and engine control

## FEATURES

- U.S. EPA-Certified
- Oil cooled light alloy pistons with high performance piston rings
- Hardened valves and valve seats
- Valley mounted water cooled exhaust manifold
- Telematics compatibility


## PSI 32LT ENGINE DATA

Model Number	32LT
Cylinders	90°, V-12
Induction System	Turbocharged & air-to-air charge-cooled
Combustion System	Spark-ignited
Cooling System	Water-cooled
Displacement	32L
Compression Ratio	10.5:1
Bore & Stroke	150 mm x 150 mm
Fuel Type	Natural Gas / Propane
Direction of Rotation	Counter-clockwise viewed on flywheel
Dry Weight	2,722 kg

## POWER RATINGS

GAS ENGINE	NG							RPM
	Gross Engine Output			Typical Generator output				
	ESP	PRP	COP	ESP	ESP	PRP	PRP	
	kWm	kWm	kWm	kWe	kVA	kWe	kVA	
32LT	600	510	357	557	696	471	589	1500
	720	612	428	661	827	559	698	1800

GAS ENGINE	LPG							RPM
	Gross Engine Output			Typical Generator output				
	ESP	PRP	COP	ESP	ESP	PRP	PRP	
	kWm	kWm	kWm	kWe	kVA	kWe	kVA	
32LT	405	344	241	364	455	307	384	1500
	475	404	283	419	524	353	442	1800



kWe values are based on standard assumptions for mechanical and electrical losses. Ratings and performance is subject to site conditions and PSI application and ratings guidelines.

