

OFF-HIGHWAY STATIONARY POWERPACK UNREGULATED

RATING CARD

AUGUST 2026

OFF-HIGHWAY STATIONARY POWERPACK UNREGULATED
RADIATOR LINEUP | 30-1866 kW



Family	Model	Rated Power	Peak Torque	Cyl	Displ. (L)	Air intake	Vcc	FIP	Throttle	Coupling	
										FWH	FW
4M06	4M06V2D0	30 kW @ 1800 rpm	159 Nm @ 1800 rpm	L4	2,3	NA	12	Mech	M	SAE 4	7.5"
	4M06V4D0	41 kW @ 1800 rpm	225 Nm @ 1400 rpm	L4	2,3	TC	12	Mech	M	SAE 3	11.5"
	4M06V6D0	47 kW @ 1800 rpm	293 Nm @ 1300 rpm	L4	2,3	TC	12	Mech	M	SAE 3	11.5"
	4M06V8D0	58 kW @ 1800 rpm	328 Nm @ 1600 rpm	L4	2,3	TCA	12	Mech	M	SAE 3	11.5"
4M08	4M08V2D0	37.2 kW @ 2500 rpm	168 Nm @ 1700 rpm	L4	3,2	NA	12	CR	ECU	SAE 3	11.5"
	4M08V4D0	45 kW @ 2500 rpm	201 Nm @ 1300 rpm	L4	3,2	NA	12	CR	ECU	SAE 3	11.5"
4M10	4M10V2D0	60 kW @ 2300 rpm	377 Nm @ 1200 rpm	L4	4,1	TC	12	Mech	M	SAE 3	11.5"
	4M10V4D0	71 kW @ 2300 rpm	406 Nm @ 1300 rpm	L4	4,1	TC	12	Mech	M	SAE 3	11.5"
4M11	4M11V2D0	62 kW @ 2200 rpm	325 Nm @ 1400 rpm	L4	4,5	TC	12	Mech	M	SAE 3	11.5"
	4M11V4D0	101 kW @ 2200 rpm	546 Nm @ 1400 rpm	L4	4,5	TCA	12	Mech	M	SAE 3	11.5"
	4M11V6D0	120 kW @ 2300 rpm	597 Nm @ 1700 rpm	L4	4,5	TCA	12	Mech	M	SAE 3	11.5"
	4M11V8D0	120 kW @ 2300 rpm	597 Nm @ 1700 rpm	L4	4,5	TCA	12	Mech	M	SAE 3	11.5"
6M11	6M11V2D0	150 kW @ 2200 rpm	823 Nm @ 1100 rpm	L6	6,8	TCA	12	Mech	M	SAE 3	11.5"
	6M11V4D0	180 kW @ 2200 rpm	900 Nm @ 1400 rpm	L6	6,8	TCA	12	Mech	M	SAE 3	11.5"
6M16	6M16V4D0	191 kW @ 2200 rpm	1266 Nm @ 1200 rpm	L6	9,7	TCA	24	Mech	M	SAE 1	14"
	6M16V6D0	240 kW @ 1800 rpm	1542 Nm @ 1200 rpm	L6	9,7	TCA	24	Mech	M	SAE 1	14"
	6M16V2D0	255 kW @ 2200 rpm	1385 Nm @ 1400 rpm	L6	9,7	TCA	24	Mech	M	SAE 1	14"
6M21	6M21V4D0	350 kW @ 1800 rpm	2154 Nm @ 1500 rpm	L6	12,5	TCA	24	Mech	M	SAE 1	14"
	6M21V2D0	370 kW @ 2200 rpm	2155 Nm @ 1300 rpm	L6	12,5	TCA	24	Mech	M	SAE 1	14"
	6M21V6D0	406 kW @ 2200 rpm	2203 Nm @ 1400 rpm	L6	12,5	TCA	24	CR	ECU	SAE 1	14"
6M33	6M33V1D0	573 kW @ 1800 rpm	3202 Nm @ 1300 rpm	L6	19,6	TCA	24	Mech	M	SAE 1	14"
	6M33V2D0	566 kW @ 1900 rpm	3412 Nm @ 1300 rpm	L6	19,6	TCA	24	CR	ECU	SAE 1	14"
	6M33V4D0	671 kW @ 1900 rpm	3937 Nm @ 1300 rpm	L6	19,6	TCA	24	CR	ECU	SAE 1	14"
8M33	8M33V2D0	785 kW @ 1900 rpm	4802 Nm @ 1400 rpm	V8	26,1	TCA	24	CR	ECU	SAE 0	18"
	8M33V4D0	902 kW @ 1900 rpm	5150 Nm @ 1400 rpm	V8	26,1	TCA	24	CR	ECU	SAE 0	18"
12M26	12M26V2D0	780 kW @ 1800 rpm	5737 Nm @ 1100 rpm	V12	31,8	TCA	24	Mech	M	SAE 0	18"
12M33	12M33V2D0	999 kW @ 1500 rpm	7997 Nm @ 1150 rpm	V12	39,2	TCA	24	CR	ECU	SAE 0	18"
	12M33V0D0	915 kW @ 1900 rpm	5205 Nm @ 1400 rpm	V12	39,2	TCA	24	CR	ECU	SAE 0	18"
	12M33V4D0	1021 kW @ 1900 rpm	6294 Nm @ 1400 rpm	V12	39,2	TCA	24	CR	ECU	SAE 0	18"
	12M33V6D0	1201 kW @ 1900 rpm	6515 Nm @ 1600 rpm	V12	39,2	TCA	24	CR	ECU	SAE 0	18"
16M33	16M33V0D0	1493 kW @ 1900 rpm	8049 Nm @ 1600 rpm	V16	52,3	TCA	24	CR	ECU	SAE 0	18"
	16M33V2D0	1716 kW @ 1900 rpm	10001 Nm @ 1600 rpm	V16	52,3	TCA	24	CR	ECU	SAE 0	18"
	16M33V4D0	1866 kW @ 1900 rpm	10501 Nm @ 1600 rpm	V16	52,3	TCA	24	CR	ECU	SAE 0	18"

L = In Line | V = V Type | NA = Naturally Aspirated | TC = Turbocharged | TCA = Turbocharged & Air Aftercooled | Vcc = DC starting voltage | Mech = Mechanical fuel injection | CR = Common Rail | M = Mechanical throttle | ECU = Electronic throttle | FWH = Flywheel Housing | FW = Flywheel

OFF-HIGHWAY STATIONARY POWERPACK UNREGULATED
HEAT EXCHANGER LINEUP | 75-445 kW



Family	Model	Continuous Power	Intermittent Power	Peak Torque	Cyl	Displ. (L)	Air intake	Vcc	FIP	Throttle	Coupling	
											FWH	FW
4M11	4M11V0D0	75 kW @ 2100 rpm	83 kW @ 2100 rpm	419 Nm @ 1100-1300 rpm	L4	4,5	TC	24	Mech	M	SAE 1	14"
	4M11V1D0	95 kW @ 2100 rpm	105 kW @ 2100 rpm	566 Nm @ 1000-1200 rpm	L4	4,5	TCA	24	Mech	M	SAE 1	14"
6M11	6M11V0D0	115 kW @ 2100 rpm	127 kW @ 2100 rpm	746 Nm @ 1100 rpm	L6	6,8	TCA	24	Mech	M	SAE 3	11.5"
	6M11V1D0	136 kW @ 2100 rpm	150 kW @ 2100 rpm	1030 Nm @ 1100 rpm	L6	6,8	TCA	24	Mech	M	SAE 3	11.5"
6M16	6M16V0D0	216 kW @ 1800 rpm	238 kW @ 1800 rpm	-	L6	9,7	TCA	24	Mech	M	SAE 1	14"
	6M16V1D0	240 kW @ 1800 rpm	264 kW @ 1800 rpm	-	L6	9,7	TCA	24	Mech	M	SAE 1	14"
6M19	6M19V0D0	288 kW @ 1800 rpm	317 kW @ 1800 rpm	-	L6	11,6	TCA	24	Mech	M	SAE 1	14"
6M21	6M21V1D0	350 kW @ 1800 rpm	385 kW @ 1800 rpm	-	L6	12,5	TCA	24	Mech	M	SAE 1	14"
	6M21V0D0	405 kW @ 1800 rpm	445 kW @ 1800 rpm	-	L6	12,5	TCA	24	CR	ECU	SAE 1	14"

L = In Line | V = V Type | NA = Naturally Aspirated | TC = Turbocharged | TCA = Turbocharged & Air Aftercooled | Vcc = DC starting voltage | Mech = Mechanical fuel injection | CR = Common Rail | M = Mechanical throttle | ECU = Electronic throttle | FWH = Flywheel Housing | FW = Flywheel

POWER

Standard ISO 3046/1 - DIN6271
Performance tolerance of ±5%

REFERENCE CONDITIONS

Air inlet temperature: 25°C
Relative humidity: 30%
Barometric pressure: 100 kPa
Derating may apply beyond these conditions

FUEL

Relative density: 0.84 kg/L
Compatible with B7 diesel EN 590

CONTACT

Société Internationale des Moteurs Baudouin
Technoparc du Brégadan
13260 Cassis
France

Moteurs Baudouin reserves the right to modify these specifications without notice. Document not contractual.